

# DECLARATION OF PERFORMANCE

## DOP N° 6 - CORIAN® EXTERIOR CLADDING

1. Unique identification code of the product type: **Corian® Sheets 12 mm (Glacier White)**
2. Type, batch or serial number or other identifier for identifying the construction product in accordance with Article 11 paragraph 4: **Corian® Sheets 12 mm (Glacier White)**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**Kits for External Wall Claddings Mechanically Fixed EAD 090062-00-0404**
4. Name, registered trade name or registered trademark and contact address of the manufacturer in accordance with Article 11 paragraph 5:  
**DuPont de Nemours International Sàrl  
154 Route du Nant d'Avril  
1217 Meyrin / SWITZERLAND**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems for evaluating and checking the constancy of performance of the construction product according to Annex V of the Construction Products Regulation:  
**System 2+**
7. In the case of a declaration of performance relating to a construction product that is covered by a harmonized standard:

The Notified Body Centre Scientifique et Technique du Bâtiment - CSTB - (N° 5-0010 rév. 33) - has issued the certificates of Factory Production Control ref. 0679-CPR-1229 for material made in USA and 0679-CPR-1300 for material made in Turkey based on:  
- Initial inspection of the factory and the factory production control  
- Ongoing surveillance, assessment and approval of factory production control

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Not applicable**
9. Declared performance:  
**Characteristic values and performance of the Corian® facade panel "Corian® EC Glacier White" as per European Technical Assessment ETA-18/0388 issued by DIBt**

Nominal sheet thickness	$h \geq$ [mm]	12.0
Char. Bending stress	[N / mm <sup>2</sup> ]	60
Average modulus of elasticity	[N / mm <sup>2</sup> ]	8500
Coefficient of thermal expansion	[1 / K]	$30.5 \times 10^{-6}$
Dead load	[kN / m <sup>2</sup> ]	0.21
10. The performance of the product according to numbers 1 and 2 corresponds to the declared performance according to number 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



**Andrea Albert**  
**Shelter Solutions EMEA Marketing Leader**  
**DuPont de Nemours International Sàrl**

02/11/2022

**Date of issue**